

TECHNICAL INFORMATION

Physical properties

Total weight: 380gsm
Vinyl Weight: 290gsm
Substrate Type: Paper
Substrate weight: 90gsm

Type II and other specifications available

Tensile Strength: MD 40 N/cm (nominal)
TD 25 N/cm (nominal)
Tear Strength: 2200 mN (nominal)

Roll size:

1.3m x 50m

Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7).
Euroclass B - s1, d0.

Adhesive:

Paper backed vinyls - Newmor Light.
Varies with substrate - please enquire

Bacteria Resistance:

Contains an active Fungicide

Light Fast:

BS EN ISO 20105 min 6

LRV

Available on Request

Specifications

Conforms to requirements of BS EN 15102, BS EN 259.

Stain/Chemical Resistance:

Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

All management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth.
5.00pm deadline for next day delivery (UK only).

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects.
Full details available on application.

Samples:

Larger samples are readily available on request.

Maintenance:

Fully washable and scrubbable. Able to withstand the use of chlorine releasing agent solutions.



FM 23833



British Product | Global Support



Newmor
WALLCOVERINGS

UK SALES:

T: 01938 551990
E: sales@newmor.com

EXPORT SALES:

T: + 44 (0) 1938 55 2671
E: enquires@newmor.com