

## TECHNICAL INFORMATION

### Physical properties

Total weight: 400g/m<sup>2</sup>

Substrate Type: Non-woven Fabric Backing

### Roll size:

126cm x 30m - cut lengths available

### Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations (Class 1, BS 476 part 7). Euroclass B - s2, d0. Class A ASTM E-84 Tunnel Test.

### Adhesive:

Newmor VOV

### Bacteria Resistance:

Contains an active fungicide

### Light Fast:

Excellent Light Fastness  
BS EN ISO 105-B02 min. 7/8

### Hanging:

Due care must be taken to ensure the wall surface is adequately prepared - it should be sound, free from dust, equal in colour and mirror smooth. This product can be hung either vertically or horizontally depending on the area being covered. Every other strip should be hung reversed to the previous regardless of vertical or horizontal installation. The joints should be overlapped by approximately 3cm then double cut. For best results use a spatula to smooth the joints, remove air bubbles and creases. Use a straight edge and sharp trimming knife at joints and corners. Do not puncture the air bubbles and do not use metal or sharp objects on the surface of the wallcovering, other than when cutting in. Only use in conjunction with dry erase pens. Clean the surface using a micro fiber cloth after each use. Do not use permanent markers or clean with any abrasive surface.

### Specifications

Conforms to requirements of BS EN 15102, BS EN 259 and WA - Quality Standard W-101.

### Stain/Chemical Resistance:

Excellent resistance to temporary staining of most staining agent and chemicals

### Quality Assurance:

All management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

### Availability:

Stocked in depth, allow 5-7 days delivery

### Origin:

Designed, manufactured and stocked in the UK

### Warranty:

Newmor offers a five year warranty against manufacturing defects. Full details available on application.

### Samples:

Larger samples are readily available on request.

### Maintenance:

Fully washable and in most cases, dirt and stains can be removed using a suitable cleaning agent or even solvent including chlorine based cleaning agents. Abrasive cleaning agents or brushes should be avoided as this may damage the integrity of the write 'n' wipe finish.



FM 23833



British Product Global Support



**Newmor**  
WALLCOVERINGS

### UK SALES:

T: 01938 551990

E: sales@newmor.com

### EXPORT SALES:

T: + 44 (0) 1938 55 2671

E: enquires@newmor.com