

Healthcare Technical Specifications

Maintenance:

Fully washable and in most cases products can be scrubbed repeatedly to remove any marks without damaging the product itself. Most products are also able to withstand the use of chlorine releasing agent solutions.

Roll size:

130cm x 30m - cut lengths available

Fire Rating:

Class 'O' to the requirements of Approved Document B of the British Building Regulations.
Euroclass B. Class A ASTM E84.

Adhesive:

Fabric backed vinyls - Newmor Heavy.
Varies with substrate - please enquire.

Bacteria Resistance:

Contains Ultrafresh antimicrobial agent.

Light Fast:

Excellent Light Fastness
BS EN ISO 105-B02 7/8

LRV = Light reflective value

Samples:

Larger samples are readily available on request.

Specifications:

Conforms to requirements of BS EN 15102, BS EN 259 and Federal Specification CCC-W-408A & C CFFA Quality Standard for Vinyl Coated Fabric Wallcoverings CFFA-W-101A

Stain/Chemical Resistance:

Pass ASTM D-1308-1987 Federal Spot Test. Resistant to temporary staining of oils, fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production procedures comply with ISO 9001, the internationally recognised Quality Standard.

Availability:

Every product stocked in depth.
5.00pm deadline for next day delivery.
(UK only)

Origin:

Designed, coloured, manufactured and stocked in the UK.

Warranty:

Newmor offers a five year warranty against manufacturing defects.
Full details available on application.