

## TECHNICAL INFORMATION

**Physical properties**

Total Weight: 460g/m<sup>2</sup> (nominal)  
 Vinyl Weight: 370g/m<sup>2</sup> (nominal)  
 Substrate Type: Polyester/Cellulose Nonwoven  
 Substrate Weight: 90g/m<sup>2</sup> (nominal)

**This product meets type II specification**

Tensile Strength: MD 80 N/cm (nominal)  
 TD 60 N/cm (nominal)  
 Tear Strength: 8500 mN (nominal)

**Roll size:**

Made to order.  
 Produced in bespoke panels or running metres.

**Pattern Repeat**

Refers to design.

**Fire Rating:**

Class B when bonded  
 To a suitable substrate  
 (Class A2 – s1,d0 or better)  
 Class A ASTM E-84 tunnel test

**Adhesive:**

Newmor Heavy.  
 Varies with substrate - please enquire.

**Bacteria Resistance:**

Contains an active Fungicide.

**Light Fast:**

Excellent Light Fastness  
 BS EN ISO 105-B02 7/8

**Light reflective value (LRV)**

Available on request.  
 In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

**Specifications**

Conforms to requirements of BS EN 15102, BS EN 259 and WA – Quality Standard W-101.

**Stain/Chemical Resistance:**

Pass ASTM D-1308-1987 Federal Spot Test.  
 Resistant to temporary staining of oils, fats, mild acids and alkalis.

**Quality Assurance:**

Our management systems and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

**Availability:**

Made to order, lead times available upon request.

**Origin:**

Designed, coloured, manufactured and stocked in the UK.

**Warranty:**

Newmor offers a five year warranty against manufacturing defects.  
 Full details available on application.

**Samples:**

Larger samples are readily available on request.

**Maintenance:**

Refer to full Digital Cleaning and Maintenance instructions, available upon request or download from the Newmor website.



This product contains at least 20% recycled material