

TECHNICAL INFORMATION

Physical properties

Total Weight: 460g/m, (nominal)
 Vinyl Weight: 370g/m, (nominal)
 Substrate Type: Nonwoven Fabric
 Substrate Weight: 90g/m, (nominal)

Tensile Strength: MD 40 N/cm (nominal)
 TD 30 N/cm (nominal)
 Tear Strength: 4500 mN (nominal)

Roll size:

130cm x 30m - cut lengths available

Fire Rating:

Class B when bonded to a suitable
 substrate ASTM E-84 Class A

Adhesive:

Fabric backed vinyls - Newmor Heavy.
 Varies with substrate - please enquire.

Bacteria Resistance:

Contains an active Fungicide.

Light Fast:

Excellent Light Fastness
 BS EN ISO 105-B02 7/8

Light reflective value (LRV)

In architecture, light reflectance value, is a
 measure of visible and usable light that is
 reflected from a surface when
 illuminated by a light source.

Specifications

Conforms to requirements of BS EN 15102,
 BS EN 259 and WA – Quality Standard W-101.

Stain/Chemical Resistance:

Resistant to temporary staining of oils,
 fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production
 procedures comply with ISO 9001 : 2015,
 the internationally recognised Quality
 Standard.

Origin:

Designed, coloured, manufactured and
 stocked in the UK.

Warranty:

Newmor offers a five year warranty
 against manufacturing defects.

Samples:

Larger samples are readily available on
 request.

Maintenance:

Fully washable and in most cases products
 can be scrubbed repeatedly to remove any
 marks without damaging the product itself.
 Also able to withstand the use of chlorine
 releasing agent solutions.

