

TECHNICAL INFORMATION

Physical properties

Total Weight: 460g/m² (nominal)
 Vinyl Weight: 355g/m² (nominal)
 Substrate Type: Nonwoven Fabric
 Substrate Weight: 105g/m² (nominal)

This Product Meets Type II Specification

Tensile Strength: MD 80 N/cm (nominal)
 TD 60 N/cm (nominal)
 Tear Strength: 8500 mN (nominal)

Roll size:

126cm x 30m - cut lengths
 available

Pattern Repeat

Vertical: 610mm
 Horizontal 1220mm
 Straight Hang, Straight Match

Fire Rating:

Class B when bonded
 To a suitable substrate
 ASTM E84 Class A

Adhesive:

Newmor Heavy.
 Varies with substrate - please enquire.

Bacteria Resistance:

Contains an active Fungicide.

Light Fast:

Excellent Light Fastness
 BS EN ISO 105-B02 7/8

Light reflective value (LRV)

Available on request.
 In architecture, light reflectance value, is a
 measure of visible and usable light that is
 reflected from a surface when illuminated
 by a light source.

Specifications

Conforms to requirements of BS EN 15102, BS
 EN 259 and WA – Quality Standard W-101.

Stain/Chemical Resistance:

Resistant to temporary staining of oils,
 fats, mild acids and alkalis.

Quality Assurance:

Our management systems and production
 procedures comply with ISO 9001 : 2015,
 the internationally recognised Quality
 Standard.

Availability:

Every product stocked in depth.
 5.00pm deadline for next day delivery.
 (UK only)

Origin:

Designed, coloured, manufactured and
 stocked in the UK.

Warranty:

Newmor offers a five year warranty
 against manufacturing defects.
 Full details available on application.

Samples:

Larger samples are readily available on
 request.

Maintenance:

Fully washable and in most cases products
 can be scrubbed repeatedly to remove any
 marks without damaging the product itself.
 Also able to withstand the use of chlorine
 releasing agent solutions.



This product contains at least 20% recycled material