

## TECHNICAL INFORMATION

**Physical properties**

Total Weight: 460g/m<sup>2</sup> (nominal)  
 Vinyl Weight: 355g/m<sup>2</sup> (nominal)  
 Substrate Type: Nonwoven Fabric  
 Substrate Weight: 105g/m<sup>2</sup> (nominal)

**This Product Meets Type II Specification**

Tensile Strength: MD 80 N/cm (nominal)  
 TD 60 N/cm (nominal)  
 Tear Strength: 8500 mN (nominal)

**Roll size:**

137cm x 27.4m - cut lengths  
 available

**Pattern Repeat**

Reverse Hang, Free Match

**Fire Rating:**

Fire Hazard Classification (ASTM E-84)  
 Flame spread: ASTM E84 Flame Spread: 25  
 Smoke density factor: 15

**Adhesive:**

Newmor Heavy.  
 Varies with substrate - please enquire.

**Bacteria Resistance:**

Mildew Resistance (anti-microbial)  
 This product exceeds G.S.A. Federal  
 Specification CCC-W-408D for Type II  
 materials using test procedures detailed  
 in Federal Specifications CCC-T-191-B.  
 Vinyl wallcoverings contain bactericides  
 and mildew inhibitors to discourage the  
 growth of mold and mildew under  
 normal conditions.

**Light Fast:**

Excellent Light Fastness  
 BS EN ISO 105-B02 7/8

**Light reflective value (LRV)**

Available on request.  
 In architecture, light reflectance value, is a  
 measure of visible and usable light that is  
 reflected from a surface when illuminated  
 by a light source.

**Specifications**

Conforms to requirements of BS EN 15102, BS  
 EN 259 and WA – Quality Standard W-101.

**Stain/Chemical Resistance:**

Resistant to temporary staining of oils,  
 fats, mild acids and alkalis.

**Quality Assurance:**

Our management systems and production  
 procedures comply with ISO 9001 : 2015,  
 the internationally recognised Quality  
 Standard.

**Availability:**

Every Product stocked in depth  
 Please allow 5/7 days for del

**Warranty:**

Newmor offers a five year warranty  
 against manufacturing defects.  
 Full details available on application.

**Samples:**

Larger samples are available on  
 request.

**Maintenance:**

Fully washable and in most cases products  
 can be scrubbed repeatedly to remove any  
 marks without damaging the product itself.  
 Also able to withstand the use of chlorine  
 releasing agent solutions.



This product contains at least 20% recycled material